



Fax 503.253.6564

**DOUBLE SPLINE AXLE ORDER FORM**

By submitting this form, customer agrees to the current Terms, Conditions, & Policies as stated in the DMI price sheets & web site

|                                                                                                            |                                                                                                     |
|------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| <b>SOLD / BILL TO:</b><br>Name _____<br>Company _____<br>Address _____<br>City _____ State _____ Zip _____ | <b>SHIP TO:</b><br>Name _____<br>Company _____<br>Address _____<br>City _____ State _____ Zip _____ |
|------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|

DAY PHONE (     ) \_\_\_\_\_ EVE PHONE (     ) \_\_\_\_\_  
 FAX (     ) \_\_\_\_\_ Email: \_\_\_\_\_ @ \_\_\_\_\_

| Qty | Description | Each | Total |
|-----|-------------|------|-------|
|     |             |      |       |
|     |             |      |       |

**Rear End** \_\_\_\_\_  
 (ie. Dana 44, Dana 60, 14 bolt, Ford 9", etc...)

**AL:** \_\_\_\_\_ **QTY:** \_\_\_\_\_  
**AL:** \_\_\_\_\_ **QTY:** \_\_\_\_\_  
**AL:** \_\_\_\_\_ **QTY:** \_\_\_\_\_  
**AL:** \_\_\_\_\_ **QTY:** \_\_\_\_\_

**Other Shaft Options:**

Seal surfaces (Requires separate drawing)  
 Threads in either end  
 3/8" NF    7/16" NF  
 Outer end    Inner end    Both ends

**S-Outer:** \_\_\_\_\_  
 (The # of splines in the drive flange)

**SL-Outer:** \_\_\_\_\_  
 (SL-Outer=The length of splines thru the drive flange, rounded to the nearest 1/16")

**S-Inner:** \_\_\_\_\_  
 (The # of splines in the diff or spool)

**SL-Inner:** \_\_\_\_\_

**Type of Diff:** \_\_\_\_\_

**Spool or Diff Manufacturer:** \_\_\_\_\_

**Axle Version:**

No outer snap ring  
 Outer snap ring  
 Dutchman specs for groove dimensions  
 Customer supplied groove dimensions

IF customer supplied groove dimensions:

**GW:** \_\_\_\_\_

**GD:** \_\_\_\_\_

**Material:**

Chromoly 4340    Hy-Tuf

