



Fax 503.253.6564

FLANGED FLOATER AXLE ORDER FORM

By submitting this form, customer agrees to the current Terms, Conditions, & Policies as stated in the DMI price sheets & web site

SOLD / BILL TO: Name _____ Company _____ Address _____ City _____ State _____ Zip _____	SHIP TO: Name _____ Company _____ Address _____ City _____ State _____ Zip _____
--	---

DAY PHONE () _____	EVE PHONE () _____
TELE FAX () _____	Email: _____

Qty	SR #	Description	Each	Total

Rear End: _____
 (ie. Dana 60, 14 bolt, ect...)

“OR”

Hybrid custom floater using:

_____ Center

_____ Spindle

(ie. Dana 60 center with GM 14 bolt spindles)

S: _____
 (S = the number of splines and carrier type; ie. locker, spool ect...)

AL: _____

AL: _____
 (AL = The length from the INSIDE flange face to the end of the splines)

Bolt Pattern: _____ on _____
 (ie. 8 holes on a 3.970” bolt circle)

Hole size: _____
 (Straight cut holes only. No taper seat)

“OR”

Stud or Bolt size: _____

Flange & Shaft Design:

Hy-Tuff, 2 Piece (Max 37 spl; 8 x 4” BC drive plate only)

1541, 1 Piece (Max 35 spl; Max 4” BC)

1541, 1 Piece (Max 37 spl; Max 4.33” BC)

4130, 1 Piece (19, 30, 33 & 35 spl; Max 4” BC)

