



OEM GMC / Chevy - Flanged Floater

1250 E Piper Ct. Meridian, ID 83642 Ph: 503.257.6604 Fax: 503.257.6564

Note: Axle lengths listed are from INSIDE of flange to end of spline

SR #	YEAR	MAKE / MODEL	REAR	OEM #	AL - LH	OEM #	AL - RH	SPL	BP	FLANGE
604	68	C20 PU w/ Leaf or Coil Springs	D60	34551-3	35 1/8	34551-3	35 1/8	30	8 x 3.720	4.503
605	67-72	K25, C20, C25 / 67 K1500 Pick-Up	D60	31494-1	34 3/4	31494-1	34 3/4	30	8 x 3.720	4.503
606	73-01	3/4T & 1T PU (1.550 Spline OD)	14B, 10.5	3977383	31 11/16	3977384	37 9/16	*30	8 x 3.562	4.460
607	87-89	C30; SRW	D70-3HD	41100-3	33 7/8	41100-2	33 3/8	35	8 x 3.562	4.460
608	88-89	C30 & K30 DRW	D70-3	41100-5	39 3/8	41100-4	38 15/16	35	8 x 3.562	4.460
609	92-02	C2500, C3500 PU / 96-98 1T Van; SRW (1.550 Spline OD) (Verify Length)	14B, 10.5	26020040	*36 11/16	26020039	32 7/16	*30	8 x 3.562	4.460
610	90-03	C1500, C2500, C3500, K1500, K2500, K3500 PU (1.550 Spline OD) (2 Piece Design)	14B, 10.5	26011161	37 9/16	26011162	41 1/2	*30	8 x 3.562	4.460
611	99-10	Silverado/Sierra 1500, 2500, 3500, Suburban 2500, Yukon XL 2500 (1.550 Spl OD)	14B, 10.5	12471329	38 5/8		33	*30	8 x 3.562	4.460
612	00-13	Silverado/Sierra 2500; SRW (1.550 Spline OD)	14B, 11.5	40003201	35 9/16	40003201	35 9/16	*30	8 x 3.562	4.460
613	00-13	Silverado/Sierra 2500; DRW Wide Track (1.550 Spline OD)	14B, 11.5	40003202	39 3/4	40003202	39 3/4	*30	8 x 3.562	4.460
614	00-13	Silverado/Sierra; DRW Narrow Track (1.550 Spline OD)	14B, 11.5	40003204	35 3/4	40003204	35 3/4	*30	8 x 3.562	4.460
615	13	Silverado 3500 (Verify year range) (1.550 Spline OD) (2 Piece Design)	14B, 11.5		40 1/4		40 1/4	*30	8 x 3.820	4.755
616	91-96	P30 Motor Home (Verify RH Length) (1.550 Spline OD)	14B, 10.5	26011811	*33 1/2	26011812	*33 1/2	*30	20T	3.770
617	79-98	P30, P300 Motor Home & Truck	D70 / D80	36625-1	36 3/16	36625-1	36 3/16	35	20T	3.770
618	92-00	P-Truck & G-Van Metric Ton / 93-99 GMT 455 / 95 MH (Verify 20 Teeth & OD)	D80	44264-1	36 3/16	44264-1	36 3/16	37	*20T	*3.900
619	94-98	P Truck / 94-99 GMT 455 Wide Track (Verify 20 Teeth & OD)	D80	44264-2	39 5/16	44264-2	39 5/16	37	*20T	*3.900
620	96-01	P Truck	D80	47037-1	36 1/4	47037-1	36 1/4	37	8 x 4.250	5.170
621	96-01	P Truck Wide Track	D80	47037-2	39 5/16	47037-2	39 5/16	37	8 x 4.250	5.170
622	00-07	P Truck & GMT 560	D80	50291-1	39 5/16	50291-1	39 5/16	37	8 x 4.250	5.170
623	03-09	GMT 610	D70	52033-4	37 1/16	52033-3	35 11/16	35	8 x 3.562	4.460
624	73-78	G300 Van / 75-78 G300 Van & C300 DRW / 73-76 C25 & C30 MH	D60/D70	36453-1	39 3/4	36453-1	39 3/4	35	8 x 3.562	4.460
625	79-92	G-Van DRW / 79-94 G300, C30 DRW, P300 UPS / 82-86 P30 MH / 84-91 RV	D60 / D70	41100-1	39 11/16	41100-1	39 11/16	35	8 x 3.562	4.460
626	88-92	G30 Van SRW / 90-92 G-Van Extended	D70-3	41100-7	36 1/2	41100-6	35 1/2	35	8 x 3.562	4.460
627	92-00	G-Van Metric Ton & P Truck (2 Piece Design)	D80	44264-1	36 3/16	44264-1	36 3/16	37	8 x 4.250	5.170
628	96-02	G-Van / 99-11 Silverado, Suburban; SRW (Verify Length) (1.550 Spline OD)	14B, 10.5	26045426	*33 7/16	26042925	39 3/16	*30	8 x 3.562	4.460
629	96-02	G-Van, P-Van, Express, Sevana; DRW (1.550 Spline OD) (2 Piece Design)	14B, 10.5	26020040	36 11/16	26042927	41 15/16	*30	8 x 3.562	4.460
630	02-09	G30 Van DRW	D70-3HD	52033-8	40 3/8	52033-7	39	35	8 x 3.562	4.460

ALL APPLICATIONS ARE APPROXIMATE AND SUBJECT TO CHANGE; REMEMBER, MEASURE TWICE AND CUT ONCE